

Line measurement of the glider with risers



Glider: Avax XC5 - 26

S/N:

Right side

Center	R-L	A	A-B	Spec.	Diff
1		7700		41	
2		7666		45	
3		7634		44	
4		7651		43	
5		7592		42	
6		7563		42	
7		7530		39	
8		7550		39	
9		7533		39	
10		7459		37	
11		7339		35	
12		7333		36	
13		7262		29	
14		7254		26	

R-L	B
	7664
	7627
	7593
	7608
	7558
	7527
	7499
	7522
	7501
	7429
	7309
	7304
	7236
	7230

R-L	C	C-B	Spec.	Diff
	7735		75	
	7698		76	
	7670		79	
	7687		77	
	7639		83	
	7621		95	
	7576		79	
	7594		79	
	7557		68	
	7486		64	
	7364		58	
	7358		58	
	7273		47	
	7256		34	

R-L	Stabilo	B14-Stabilo	Spec.	Diff
	6923		301	
	6909		318	
	6804		421	
	6801		418	
	6829		398	
	6857		365	

R-L	Brakes
	8013
	7703
	7508
	7426
	7303
	7183
	7181
	7203
	7138
	7091
	7073
	7095

Left side

Center	L-R	A	A-B	Spec.	Diff
1		7700		41	
2		7666		45	
3		7634		44	
4		7651		43	
5		7592		42	
6		7563		42	
7		7530		39	
8		7550		39	
9		7533		39	
10		7459		37	
11		7339		35	
12		7333		36	
13		7262		29	
14		7254		26	

L-R	B
	7664
	7627
	7593
	7608
	7558
	7527
	7499
	7522
	7501
	7429
	7309
	7304
	7236
	7230

L-R	C	C-B	Spec.	Diff
	7735		75	
	7698		76	
	7670		79	
	7687		77	
	7639		83	
	7621		95	
	7576		79	
	7594		79	
	7557		68	
	7486		64	
	7364		58	
	7358		58	
	7273		47	
	7256		34	

L-R	Stabilo	B14-Stabilo	Spec.	Diff
	6923		301	
	6909		318	
	6804		421	
	6801		418	
	6829		398	
	6857		365	

R-L	Brakes
	8013
	7703
	7508
	7426
	7303
	7183
	7181
	7203
	7138
	7091
	7073
	7095

Tolerance: +/- 10 mm

Spec. = Recommended differences between rows

Measured by:	
Created by:	Lukas Pohl, 7.12.2016