

# Lines measurement of the referential glider



gradient

Glider: **Bright5 24**

S/N:

G38241312009

Left side

Center	L-R	A	A-B	Spec.	Diff	Ø
1	2	6650	76	72	4	
2	-3	6593	73	73	0	1
3	0	6563	73	74	-1	
4	4	6587	71	72	-1	
5	1	6565	69	70	-1	
6	4	6526	67	68	-1	-3
7	6	6510	62	63	-1	
8	-1	6521	51	58	-7	
9	2	6467	45	43	2	
10	-1	6411	28	34	-6	-2
11	1	6352	19	19	0	
12	-1	6326	12	14	-2	
13	1	6100	-16	-12	-4	
S	4	5968	1	0	1	

L-R	B
0	6574
2	6520
-3	6490
-1	6516
0	6496
2	6459
4	6448
-1	6470
-3	6422
0	6383
-2	6333
1	6314
2	6116
3	5967

L-R	C	C-B	Spec.	Diff	Ø
-8	6649	75	75	0	
1	6596	76	75	1	1
1	6567	77	76	1	
0	6593	77	75	2	
2	6568	72	73	-1	
4	6532	73	74	-1	-3
2	6516	68	73	-5	
4	6538	68	71	-3	
2	6467	45	40	5	
2	6427	44	39	5	2
2	6361	28	31	-3	
5	6336	22	22	0	
-1	5993	26	30	-4	

L-R	D	D-B	Spec.	Diff	Ø
3	6746	172	164	8	
-1	6691	171	165	6	5
-4	6653	163	162	1	
0	6679	163	158	5	
-2	6650	154	156	-2	
1	6614	155	155	0	-2
-2	6591	143	147	-4	
-5	6608	138	140	-2	
2	6519	97	92	5	
7	6474	91	87	4	3
5	6404	71	67	4	
3	6366	52	52	0	
1	6059	92	90	2	

Spec.	Brakes	Diff
6700	6690	-10
6460	6456	-4
6380	6374	-6
6287	6280	-7
6210	6205	-5
6264	6258	-6
6273	6269	-4
6282	6278	-4
6300	6297	-3

Riser: B

Glider: **Bright5 24**

S/N:

G38241312009

Right side

Center	L-R	A	A-B	Spec.	Diff	Ø
1	-2	6648	74	72	2	-1
2	3	6596	78	73	5	
3	0	6563	70	74	-4	
4	-4	6583	66	72	-6	
5	-1	6564	68	70	-2	
6	-4	6522	65	68	-3	-4
7	-6	6504	60	63	-3	
8	1	6522	51	58	-7	
9	-2	6465	40	43	-3	
10	1	6412	29	34	-5	-3
11	-1	6351	16	19	-3	
12	1	6327	14	14	0	
13	-1	6099	-15	-12	-3	
S	-4	5964	0	0	0	

L-R	B
0	6574
-2	6518
3	6493
1	6517
0	6496
-2	6457
-4	6444
1	6471
3	6425
0	6383
2	6335
-1	6313
-2	6114
-3	5964

L-R	C	C-B	Spec.	Diff	Ø
8	6657	83	75	8	
-1	6595	77	75	2	2
-1	6566	73	76	-3	
0	6593	76	75	1	
-2	6566	70	73	-3	
-4	6528	71	74	-3	-4
-2	6514	70	73	-3	
-4	6534	63	71	-8	
-2	6465	40	40	0	
-2	6425	42	39	3	-2
-2	6359	24	31	-7	
-5	6331	18	22	-4	
1	5994	30	30	0	

L-R	D	D-B	Spec.	Diff	Ø
-3	6743	169	164	5	
1	6692	174	165	9	5
4	6657	164	162	2	
0	6679	162	158	4	
2	6652	156	156	0	
-1	6613	156	155	1	1
2	6593	149	147	2	
5	6613	142	140	2	
-2	6517	92	92	0	
-7	6467	84	87	-3	-2
-5	6399	64	67	-3	
-3	6363	50	52	-2	
-1	6058	94	90	4	

Spec.	Brakes	Diff
6700	6688	-12
6460	6448	-12
6380	6374	-6
6287	6278	-9
6210	6207	-3
6264	6258	-6
6273	6266	-7
6282	6281	-1
6300	6295	-5

Riser: B

Recommended differences between rows  
Tolerance: +/- 10 mm

Measured by:  
Date: